
KL3140

DIP8 IGBT/MOSFET

0.6A Output Current GATE DRIVER

PHOTOCOUPLER

0.6A峰值输出门极驱动光耦



＊本文档中包含的信息反映了具有代表性的使用场景，仅供技术参考。
The information contained in this document reflects representative usage scenarios and is intended for technical reference only.
＊本文档中提到的产品型号和规格如有更改或改进，恕不另行通知。在生产使用之前，客户应参考产品规格书的最新数据表。
Product models and specifications mentioned in this document are subject to change or improvement without notice. Customers should refer to the latest data sheets in the product specifications prior to production use.
＊在使用本文档中引用的产品时，请确保产品在数据手册中规定的环境和电气限制范围内运行。如果客户使用超过指定的限制，晶台微电子将不会对任何后续问题负责。
When using the products referenced in this document, ensure that the products are operated within the environmental and electrical limits specified in the data sheet. If the customer uses the product beyond the specified limits, Kinglight Microelectronics will not be responsible for any subsequent problems.
＊本文档中的信息适用于电子元器件应用中的典型用法。如有任何特殊用途，请向晶台微电子咨询，以获得进一步的帮助。
The information in this document applies to typical use in electronic component applications. For special applications, please contact Kinglight Microelectronics for further assistance.
＊未经晶台微电子允许，不得复制或转载本文件的内容和信息。对于最新的信息，请参考官方网站 Http://www.klmicro.com。
The contents and information in this document may not be copied or reproduced without the permission of Kinglight Microelectronics. For the latest information, please visit the official website Http://www.klmicro.com.

1. 产品特点 Product features

- 轨到轨输出电压 Rail-to-rail output voltage
- 可保证在-40至110℃温度范围内运行 Guaranteed performance from -40°C to 110°C
- 最大峰值输出电流0.6A Peak Output Current : I_{OP} = 0.6A (max)
- 最大阈值输入电流5mA Threshold Input Current: I_{FLH}=5mA (max)
- 输入与输出间高隔离电压(Viso=5000 V rms)
  High isolation voltage between input and output (Viso=5000 V rms)
- 无Pb且符合ROHS标准 Pb free and RoHS compliant
- 安全审批 Safety approval
  CQC认证已批准(编号:CQC26001516435) CQC approved (No.CQC26001516435)

2. 产品描述 Product Description


- KL3140由一个红外发光二极管和集成的高增益高速光电探测器组成,该器件采用 8 引脚 DIP 封装。
  The KL3140 consists of an infrared light emitting diode and integrated high gain, high-speed Photo detectors. The device is housed in an 8 pin DIP package.
- 光电检测器有一个内部屏蔽，可确保共模瞬态抗扰度为±25 kV/μs。适用于IGBT或功率MOSFET的栅极驱动电路。
  The photo detector has an internal shield that provides guaranteed common-mode transient Immunity of ±25 kV/μs. It is suitable for direct gate driving circuit for IGBTs or power MOSFETs.

3. 产品应用 Product Applications

- 隔离式IGBT/Power MOSFET栅极驱动 Isolated IGBT/Power MOSFET Gate Drive
- 不间断供电系统 Uninterruptible power supply
- 逆变器 Inverters
- 家用电器，如暖风机等 Home appliances, such as fan heaters, etc.

4. 功能图 Functional Diagram

示意图 Schematic



引脚配置 Pin Configuration

1. 无连接 No Connection
2. 阳极 Anode
3. 阴极 Cathode
4. 无连接 No Connection
5. 电源电压 V_{EE}
6. 输出电压 V_{OUT}
7. 无连接 No Connection
8. 电源电压 V_{CC}

注意：引脚8和5之间必须连接一个 0.1μF 旁路电容器

Note： A 0.1μF bypass capacitor must be connected between pins 8 and 5

5. 光电特性 Electrical-Optical characteristics

• 最大限度额定值(温度=25℃) Absolute Maximum Ratings(Ta=25℃)

参数 Parameter		符号 Symbol	额定值 Rated Value	单位 Unit
输入 Input	正向电流 Forward current	I_F	25	mA
	正向脉冲电流 Pulse Forward current(1*)	I_{FP}	1	A
	反向电压 Reverse voltage	V_R	5	V
输出 Output	“H” 峰值输出电流 “H” Peak Output current	I_{OPH}	0.6	A
	“L” 峰值输出电流 “L” Peak Output current	I_{OPL}	0.6	A
	输出电压 Peak Output voltage	V_O	30	V
	工作电压 Supply voltage	V_{CC}-V_{EE}	15 to 30	V
工作频率 Operating Frequency		f	50	kHz
隔离电压 (2*) Isolation Voltage		V_{ISO}	5000	Vrms
总功耗 Total Power Dissipation		P_T	300	mW
工作温度 Operating temperature		T_{OPR}	-40 to +110	℃
储存温度 Storage temperature		T_{STG}	-55 to +125	℃
焊接温度 (3*) Soldering temperature		T_{SOL}	260	℃

附注 (Notes):

1* 脉冲宽度 ≤ 1μs、300pps Pulse width ≤ 1μs, 300pps

2* 交流电源1分钟内, 相对湿度在40~60%RH环境下, 隔离电压测试时, 1、2、3和4脚短接在一起,, 5、6、7和8脚短接在一起

AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1 to 4 are shorted together, and pins 5 to 8 are shorted together.

3* 焊接时间为10秒 Soldering time is 10 seconds

6. 电气特性(Ta=-40至110℃,除非另有规定)

Electrical Characteristics(Ta=-40 to 110℃ unless specified otherwise)

参数 Parameter		符号 Symbol	最小值 Min.	规格值 Typ.	最大值 Max.	单位 Unit	条件 Condition
输入 Input	正向电压 Forward voltage	V_F	-	-	1.8	V	I_F=10mA
	反向电压 Reverse voltage	V_R	5.0	-	-	V	I_R=10μA
输出 Output	高电平电源电流 High level supply current	I_{CCH}	-	1.6	3.2	mA	I_F=0mA, V_{CC}=30V V_O=Open
	低电平电源电流 Low level supply current	I_{CCL}	-	2.0	3.2	mA	

• 传输特性 Transfer Characteristics

参数 Parameter	符号 Symbol	最小值 Min.	规格值 Typ.*	最大值 Max.	单位 Unit	条件 Condition
高电平输出电流(4*) HIGH Level Output Current	I_{OH}	-	-0.6	-0.2	A	V_{CC}=30V, I_F=10mA V_O= V_{CC} -1V
		-	-	-0.6		V_{CC}=30V, I_F=10mA V_O= V_{CC} -4V
低电平输出电流(4*) LOW Level Output Current	I_{OL}	0.2	0.6	-	A	V_{CC}=30V, I_F=0mA V_O= V_{EE} +1V
		0.6	-	-		V_{CC}=30V, I_F=0mA V_O= V_{EE} +4V
高电平输出电压 HIGH Level Output Voltage	V_{OH}	V_{CC}-4	-	-	V	V_{CC}= 30V, I_F=10mA I_O=-0.6A
		V_{CC}-0.5	-	-		V_{CC}= 30V, I_F=10mA I_O=-100mA
低电平输出电压 LOW Level Output Voltage	V_{OL}	-	-	V_{CC}+4	V	V_{CC}= 30V, I_F=10mA I_O=0.6A
		-	-	V_{EE}+0.5		V_{CC}= 30V, I_F=10mA I_O=100mA
输入阈值电流 Input Threshold Current	I_{FLH}	-	1.5	5	mA	V_{CC}=15 or 30V, V_O >5V
输入阈值电压 Input Threshold Voltage	V_{FLH}	0.8	-	-	V	V_{CC}=15 or 30V, V_O <5V
低电压锁定阈值 Under Voltage Lockout Threshold	V_{UVLO+}	11.0	-	13.5	V	I_F=10mA V_O >5V
低电压锁定阈值 Under Voltage Lockout Threshold	V_{UVLO-}	10	-	12.5	V	I_F=10mA V_O <5V

开关特性 Switching Characteristics

参数 Parameter	符号 Symbol	最小值 Min.	规格值 Typ.*	最大值 Max.	单位 Unit	条件 Condition
低电平传输延迟 Propagation Delay Time to output Low level	T_{PHL}	50	90	300	ns	I_F=7 to 16mA V_{CC}=15 or 30V R_G=10Ω，C_G=10nF f=10kHz, T_A=25°C Duty Cycle=50%
高电平传输延迟 Propagation Delay Time to output High level	T_{PLH}	50	125	300	ns	
脉冲宽度失真 Pulse width distortion	$\|T_{PHL}-T_{PLH}\|$	-	-	100	ns	
传播延迟偏差(5*) Propagation Delay Skew	t_{PSK}	-	-	150	ns	
输出上升时间 Output rise time	tr	-	50	-	ns	
输出下降时间 Output fall time	tf	-	50	-	ns	
输出高电平共模抑制(6*) Common Mode Transient Immunity at Logic High	CM_H	25	-	-	kV/us	I_F=10mA,V_{CC}=30V, V_{CM}=1500V, T_A=25°C
输出低电平共模抑制(7*) Common Mode Transient Immunity at Logic Low	CM_L	25	-	-	kV/us	I_F=0mA,V_{CC}=30V, V_{CM}=1500V, T_A=25°C

附注 (Notes):

4* 最大脉冲宽度10μs，最大占空比1% Max pulse width=10μs, max duty cycle =1%

5* 传输延迟偏差的定义是最大和最小传输延迟时间的差值(即 T_{PHL}或 T_{PLH}之差)，在相同的测试条件(电源电压、输入电流、温度等)下对产品进行评估。

Propagation delay skew is defined as the difference between the largest and smallest propagation delay times (i.e. T_{PHL} or T_{PLH}) of multiple samples. Evaluations of these samples are conducted under identical test conditions (supply voltage, input current, temperature, etc).

6* 输出高电平共模抑制是共模脉冲信号 V_{CM} 后沿的最大可容电压上升率 dv/dt，使输出保持高电平(即 V_O>15.0V)

Common mode transient immunity at output high is the maximum tolerable negative dv/dt on the trailing edge of the common mode impulse signal, V_{CM}, to assure that the output will remain high (i.e. V_O >15.0V)

7* 输出低电平共模抑制是共模脉冲信号 V_{CM} 前沿的最大可容电压上升率 dv/dt，使输出保持低电平(即 V_O <1.0V)

Common mode transient immunity at output low is the maximum tolerable positive dv/dt on the leading edge of the common mode pulse signal, VCM, to assure that the output will remain low (i.e. V_O <1.0V)

7. 特性曲线 Characteristic Curves

图1. 正向电压和环境温度的关系

Fig 1. Forward Voltage vs Ambient Temperature




图2. 输出高电压和输出高电流的关系

Fig.2 Output High Voltage vs Output High Current




图3. 输出高压降和环境温度的关系

Fig 3. Output High Voltage Drop vs Ambient Temperature




图4. 输出低电压和输出低电流的关系

Fig 4. Output Low Voltage Vs Output Low Current




图5. 低电压输出和环境温度的关系

Fig 5. Output Low Voltage vs Ambient Temperature




图6. 供电电流和环境温度的关系

Fig 6. Supply Current vs Ambient Temperature




图7. 供电电流和电源电压的关系

Fig 7. Supply Current vs Supply voltage




图8. 阈值输入电流环境温度的关系

Fig 8. Threshold Input Current vs Ambient Temperature




图9. 欠压闭锁

Fig 9. Under Voltage Lockout




图10. 传播延迟和电源电压的关系

Fig 10. Propagation Delay vs Supply Voltage




图11. 传播延迟和正向电流的关系

Fig 11. Propagation Delay vs LED Forward Current




图12. 传播延迟和环境温度的关系

Fig 12. Propagation Delay vs Ambient Temperature




图13. 传播延时和负载电阻的关系

Fig 13. Propagation Delay vs Series Load Resistance




图14. 传播延时和负载电容的关系

Fig 14. Propagation Delay vs Load Capacitance




图15.I_{OH}测试电路

Fig 15. I_{OH} Test circuit




图16. I_{OL}测试电路

Fig 16. I_{OL} Test circuit




图17.V_{OH}测试电路

Fig 17. V_{OH} Test circuit




图18. V_{OL}测试电路

Fig 18. V_{OL} Test circuit




图19.I_{FHL}测试电路

Fig 19. I_{FHL}e Test circuit




图20. UVLO测试电路

Fig 20. UVLO Test circuit




图21.开关时间测试电路

Fig 21. Switching Time Test circuit





图22.CMR 测试电路

Fig 22. CMR Test circuit



8. 订单信息 Order Information

• 材料编号 Part Number

KL3140Y-Z-V

附注(Notes):

Y =引脚形式选项(S、S1、M 或 无)
Lead form option (S, S1, M or none)


Z = 料带和卷轴选项(TA, TB或无)
Tape and reel option (TA、TB or none)

V = 表示VDE标识(客户指定镭射字符才加"V")
VDE (Only add "V" to laser characters specified by the customer)


选项 Option	描述 Description	包装数量 Packing quantity
无 None	标准DIP-8 Standard DIP-8	每管45pcs 45 units per tube
M	宽引脚弯曲(0.4英寸间距) Wide lead bend (0.4 inch spacing)	每管45pcs 45 units per tube
S-TA	表面贴装引线形式+TA载带和卷轴选项 Surface mount lead form + TA tape & reel option	每卷1000pcs 1000 units per reel
S-TB	表面贴装引线形式+TB载带和卷轴选项 Surface mount lead form + TB tape & reel option	每卷1000pcs 1000 units per reel
S1-TA	表面贴装引线形式(低剖面)+TA载带和卷轴选项 Surface mount lead form (low profile) + TA tape & reel option	每卷1000pcs 1000 units per reel
S1-TB	表面贴装引线形式(低剖面)+TB载带和卷轴选项 Surface mount lead form (low profile) + TB tape & reel option	每卷1000pcs 1000 units per reel

9. 封装尺寸(单位:毫米) Package Drawing(Unit:mm)


• 标准DIP型号 Standard DIP Type




• 选择M型号 Option M Type




• 选择S型号 Option S Type



• 选择S1型号 Option S1 Type



• 表面贴片类型PIN脚焊盘布局 Surface patch type PIN foot pad layout





备注 Notes

a. 建议焊盘尺寸仅供参考Suggested pad dimension is just for reference only

b.请根据个人需要修改焊盘尺寸Please modify the pad dimension based on individual needs

10.设备标记 Device marking






(范本参考 Template reference)

附注(Notes):

KL	= 表示晶台微电子有限公司 Denotes Kinglight Microelectronics
3140	= 表示材料部件号 Denotes Device Part Number
Y	= 表示1位年份代码Denotes 1 digit Year code
WW	= 表示2位周别代码Denotes 2 digit Week code
V	= 表示VDE标识(客户指定镭射字符才加"V") VDE (Only add "V" to laser characters specified by the customer)


11.料带和卷轴包装规格 Tape & Reel Packing Specifications

• 选择TA Option TA




卷轴进给方向 Direction of feed from reel

• 选择TB Option TB



卷轴进给方向 Direction of feed from reel

料带尺寸Material belt size




尺寸编号 Dimension No.	A	B	D0	D1	E	F
尺寸(mm) Dimension(mm)	10.4±0.1	10.0±0.1	1.5±0.1	1.5±0.3	1.75±0.1	7.5±0.1
尺寸编号 Dimension No.	P_0	P1	P2	t	W	K
尺寸(mm) Dimension(mm)	4.0±0.1	12.0±0.1	2.0±0.1	0.4±0.1	16.0±0.5	4.5±0.1

12.焊接温度曲线 Temperature Profile Of Soldering

• 回流焊温度曲线 Reflow soldering

建议在下面所示的温度和时间分布条件下, 进行一次回流焊作业, 不得超过三次

One time soldering reflow is recommended within the condition of temperature and time profile shown below. Do not solder more than three times.




项目 Item	符号 Symbol	最小值 Min.	最大值 Max.	单位 Unit
预热温度 Preheat Temperature	T_s	150	200	℃
预热时间 Preheat Time	ts	60	120	s
升温速率 Ramp-Up Rate (T_L to T_P)	-	-	3	℃/s
液相线温度 Liquidus Temperature	T_L	217		℃
高于液相线温度(T_L)的时间 Time above Liquidus Temperature T_L	t_L	60	100	s
峰值温度 Peak Temperature	T_P	-	260	℃
T_c 在(T_P-5)和 T_P之间的时间 Time During Which T_c Is Between (T_P-5) and T_P	t_p	-	30	s
降温速率 Ramp-down Rate(T_P to T_L)	-	-	6	℃/s

• 波峰焊温度曲线 Wave Soldering

温度条件下, 建议一次焊接

One time soldering is recommended within the condition of temperature



温度 Temperature	260℃+0/-5℃
时间 Time	10秒 10S
预热温度 Preheat temperature	25至140℃ 25 to 140℃
预热时间 Preheat time	30至80秒 30 to 80 S