
Kinglight®
晶台微电子

KL3H7U

PHOTO TRANSISTOR

SSOP4 晶体管光耦(车规)



* 本文档中包含的信息反映了具有代表性的使用场景，仅供技术参考。
  The information contained in this document reflects representative usage scenarios and is intended for technical reference only.
* 本文档中提到的产品型号和规格如有更改或改进，恕不另行通知。在生产使用之前，客户应参考产品规格书的最新数据表。
  Product models and specifications mentioned in this document are subject to change or improvement without notice. Customers should refer to the latest data sheets in the product specifications prior to production use.
* 在使用本文档中引用的产品时，请确保产品在数据手册中规定的环境和电气限制范围内运行。如果客户使用超过指定的限制，晶台微电子将不会对任何后续问题负责。
  When using the products referenced in this document, ensure that the products are operated within the environmental and electrical limits specified in the data sheet. If the customer uses the product beyond the specified limits, Kinglight Microelectronics will not be responsible for any subsequent problems.
* 本文档中的信息适用于电子元器件应用中的典型用法。如有任何特殊用途，请向晶台微电子咨询，以获得进一步的帮助。
  The information in this document applies to typical use in electronic component applications. For special applications, please contact Kinglight Microelectronics for further assistance.
* 未经晶台微电子允许，不得复制或转载本文件的内容和信息。对于最新的信息，请参考官方网站 Http://www.klmicro.com。
  The contents and information in this document may not be copied or reproduced without the permission of Kinglight Microelectronics. For the latest information, please visit the official website Http://www.klmicro.com.

1. 产品特点 Product features

- 电流转换率(Current transfer ratio)
  CTR: 50~600% at I_F =0.5mA, V_{CE} =5V
- 输入与输出间高隔离电压(Viso=3750 V rms)
  High isolation voltage between input and output (Viso=3750 V rms)
- 工作温度(-55℃~+125℃) Operating temperature (-55℃~+125℃)
- 外形为2.0mm的紧凑型4pin SSOP
  Compact 4 Pin SSOP with a 2.0 mm profile
- 符合无卤素(溴<900ppm, 氯<900ppm, 溴+氯<1500ppm)
  Compliance Halogen Free (Br < 900ppm, Cl < 900ppm, Br+Cl < 1500ppm)
- 符合欧盟REACH法规 Compliance with EU REACH
- 无Pb且符合ROHS标准 Pb free and compliant with RoHS standards
- AEC-Q102认证 AEC-Q102 qualified
- 安全审批 Safety approval
  CQC认证已批准(编号:CQC25001468787) CQC approved (No.CQC25001468787)
  UL认证已批准 (编号: UL-US-2555217-0) UL approved (No.UL-US-2555217-0)
  VDE认证已批准(编号:40061363) VDE approved (No.40061363)


2. 产品描述 Product Description

- KL3H7U型是由一个红外发射二极管和光电晶体管构成光电耦合器
  The KL3H7U series devices consist of an infrared emitting diode, optically coupled to a phototransistor detector encapsulated with green compound.
- 它们是4引脚小外形SMD封装.
  They are packaged in a 4-pin small outline SMD package

3. 产品应用 Product Applications

- DC-DC转换器、可编程序控制器 DC-DC Converters、Programmable controllers
- 电信设备 Telecommunication equipment
- 不同电位,不同阻抗的电路之间的信号传输
  Signal transmission between circuits of different potentials and impedances

4. 功能图 Functional Diagram



引脚配置 Pin Configuration
1. 阳极 Anode
2. 阴极 Cathode
3. 发射极 Emitter
4. 集电极 Collector

5. 光电特性 Electrical-Optical characteristics

• 最大限度额定值(温度=25ºC) Absolute Maximum Ratings(Ta=25ºC)

参数 Parameter		符号 Symbol	额定值 Rated Value	单位 Unit
输入 Input	正向电流 Forward current	I_F	60	mA
	反向电压 Reverse voltage	V_R	5	V
	功耗 Power dissipation	P_D	40	mW
输出 Output	集电极电流 Collector current	I_C	30	mA
	集电极-发射极电压 Collector and emitter Voltage	V_{CEO}	80	V
	发射极-集电极电压 Emitter and Collector Voltage	V_{ECO}	5	V
	功耗 Power dissipation	P_C	150	mW
总功耗 Total Consume Power		P_{TOT}	200	mW
隔离电压 (1*) Isolation Voltage		V_{ISO}	3750	Vrms
工作温度 Operating temperature		T_{OPR}	-55 to +125	℃
储存温度 Storage temperature		T_{STG}	-55 to +150	℃
焊接温度(2*) Soldering temperature		T_{SOL}	260	℃

附注(Notes):

1* 交流电源1分钟内, 相对湿度40~60%环境下, 隔离电压测试方法, 引脚1&2短接在一起, 引脚3&4短接在一起
AC for 1 minute, 40~60%RH in this test, Pins 1 and 2 are shorted together, and pins 3 and 4 are shorted together

2* 焊接时间为10秒 Soldering time is 10 seconds

6. 电气特性(Ta=25℃,除非另有规定)

Electrical Characteristics(Ta=25℃ unless specified otherwise)

参数 Parameter		符号 Symbol	最小值 Min.	规格值 Typ.	最大值 Max.	单位 Unit	条件 Condition
输入 Input	正向电压 Forward voltage	V_F	-	1.3	1.7	V	I_F=1mA
	反向电流 Reverse current	I_R	-	-	10	μA	V_R=5V
	输入电容 Input capacitance	C_{in}	-	30	250	pF	V=0, f=1kHz
输出 Output	集电极暗电流 Collector-Emitter dark current	I_{CEO}	-	-	100	nA	V_{CE}=20V I_F =0mA
	集电极-发射极击穿电压 Collector-Emitter breakdown voltage	V_{CEO}	80	-	-	V	I_C=0.1mA I_F=0mA
	发射极-集电极击穿电压 Emitter-Collector breakdown voltage	V_{ECO}	5	-	-	V	I_E=0.1mA I_F=0mA
传输特性 Transfer Characteristics	集电极-发射极饱和压降 Collector-Emitter saturation voltage	$V_{CE(sat)}$	-	-	0.4	V	I_F=3mA I_C=1.6mA
	隔离电阻 Isolation resistance	R_{ISO}	$5x10^{10}$	-	-	Ω	V_{IO}=500Vdc 40~60% R.H.
	浮动电容 Floating capacitor	C_f	-	0.3	1.0	pF	V_{IO}=0V f=1MHz
	上升时间 Response Time (Rise)	t_r	-	8	-	μs	V_{CE}=2V I_C=2mA R_L=100Ω
	下降时间 Response Time (Fall)	t_f	-	10	-	μs	

• 温度Ta=25℃下规格值 Typical values at Ta = 25°C

• 传输特性等级表(Ta=25℃, 除非另有规定)

Transfer Characteristics level table (Ta=25℃ unless specified otherwise)

参数 Parameter		符号 Symbol	最小值 Min.	规格值 Typ.	最大值 Max.	单位 Unit	条件 Condition
电流传输比 Current transfer ratio	KL3H7U	CTR	50	-	600	%	I_F=0.5mA V_{CE}=5V
	KL3H7U-A		100	-	200		
	KL3H7U-B		150	-	300		
	KL3H7U-C		200	-	400		

7. 特性曲线 Characteristic Curves

图 1.正向电流与正向电压曲线图
Figure1.Forward Current vs Forward Voltage




图 2.集电极电流与正向电流曲线图
Figure2.Collector Current vs Forward Current




图 3.电流传输比与正向电流曲线图
Figure3. Normalized Current Transfer Ration vs Forward Current




图4. 集电极电流 vs 集电极-发射极电压曲线图
Figure4. Collector Current vs Collector-Emission Voltage




图 5. 集电极电流 vs 集电极-发射极电压曲线图
Figure5. Collector Current vs Collector-Emission Voltage




图 6.集电极电流与环境温度曲线图
Figure6. Collector Current vs Ambient Temperature,




图 7.电流传输比与环境温度曲线图
Figure7. Current Transfer Ration vs Ambient Temperature




图 8. 集电极暗电流与环境温度曲线图
Figure8. Dark Current vs Ambient Temperature




图 9. 响应时间和负载电阻曲线图
Figure9. Switching Time vs Load Resistance




图 10. 集电极-发射极饱和电压与环境温度曲线图
Figure10. Collector-Emitter Saturation Voltage vs Ambient Temperature





图 11. 开关时间测试电路及波形
Figure11. Switching Time Test Circuit & Waveforms



8. 订单信息 Order Information

• 零件编号 Part Number


KL3H7U-X-Y-V

附注(Notes):


X = 表示CTR等级(A、B、C 或 无)
CTR Rank (A, B, C or none)
Y = 载带和卷轴包装方式(TA、TB)
Tape and reel option (TA, TB)
V =表示VDE标识(客户指定镭射字符才加"V")
VDE (Only add "V" to laser characters specified by the customer)

选项 Option	描述 Description	包装数量 Packing quantity
TA	TA料带 & 卷轴选择 TA tape & reel option	每卷6000pcs 6000 units per reel
TB	TB料带 & 卷轴选择 TB tape & reel option	每卷6000pcs 6000 units per reel
TA-V	TA料带 & 卷轴选择+VDE TA tape & reel option+VDE	每卷6000pcs 6000 units per reel
TB-V	TB料带 & 卷轴选择+VDE TB tape & reel option+VDE	每卷6000pcs 6000 units per reel
/	内盒装:每盒3卷 Inner box packaging:3 reels/box	每盒18 Kpcs 18 Kpcs per box
/	每箱装:10个内盒 Pack per Carton:10 inner boxes	每箱180 Kpcs 180 Kpcs per reel Carton

9. 封装尺寸(单位:毫米) Package Drawing(Unit:mm)



• 表面贴装引线框架及推荐焊盘布局 Recommended pad layout for surface mount lead frame



附注(Notes):

a. 推荐焊盘尺寸仅供参考 Suggested pad dimension is just for reference only

b. 请根据个人需要修改焊盘尺寸 Please modify the pad dimension based on individual needs

10. 设备标记 Device marking





(范本参考 Template reference)

附注(Notes):

KL = 表示晶台微电子有限公司 Denotes Kinglight Microelectronics

3H7U = 表示材料部件号 Denotes Device Part Number

R = 表示CTR等级(A、B、C 或 无)
CTR Rank (A, B, C or none)


Y = 表示1位年份代码 Denotes 1 digit Year code

WW = 表示2位周别代码 Denotes 2 digit Week code

V = 表示VDE标识(客户指定镭射字符才加"V")
VDE (Only add "V" to laser characters specified by the customer)


11. 料带和卷轴包装规格 Tape & Reel Packing Specifications

• 选择TA Option TA




卷轴进给方向 Direction of feed from reel

• 选择TB Option TB



卷轴进给方向 Direction of feed from reel

料带尺寸Material belt size




尺寸编号 Dimension No.	A0	B0	D0	D1	E	F
尺寸(mm) Dimension(mm)	3.0±0.10	7.45±0.1	1.5+0.10/-0	1.5±0.10	1.75±0.1	5.5±0.1
尺寸编号 Dimension No.	P0	P1	P2	t	W	K0
尺寸(mm) Dimension(mm)	4.0±0.15	8.0±0.1	2.0±0.10	0.3±0.05	12.1±0.2	2.45±0.1

12. 焊接温度曲线 Temperature Profile Of Soldering

• 回流焊温度曲线 Reflow soldering

建议在下面所示的温度和时间分布条件下, 进行一次回流焊作业, 不得超过三次

One time soldering reflow is recommended within the condition of temperature and time profile shown below. Do not solder more than three times.



项目 Item	符号 Symbol	最小值 Min.	最大值 Max.	单位 Unit
预热温度 Preheat Temperature	T_s	150	200	℃
预热时间 Preheat Time	ts	60	120	s
升温速率 Ramp-Up Rate (T_L to T_P)	-	-	3	℃/s
液相线温度 Liquidus Temperature	T_L	217		℃
高于液相线温度(T_L)的时间 Time above Liquidus Temperature T_L	t_L	60	100	s
峰值温度 Peak Temperature	T_P	-	260	℃
T_c 在(T_P-5)和 T_P之间的时间 Time During Which T_c Is Between (T_P-5) and T_P	t_p	-	30	s
降温速率 Ramp-down Rate(T_P to T_L)	-	-	6	℃/s